

WLAN / Wi-Fi / Wimax Directional YAGI Antenna

- Frequency: 2.4 / 3.5 / 5.8 GHz
- Gain: 12 / 15 / 18 dBi
- POLARIZATION: VERTICAL
- V.S.W.R. LESS THAN 1.5
- POWER CAPACITY: 50 WATTS
- IMPEDANCE: 50 OHM

- BEAM WIDTH :

	12dBi	15dBi	18dBi
VERTICAL	35°	28°	23°
HORIZONTAL	40°	28°	24°

- N FEMALE CONNECTOR
- OPERATING TEMPERATURE: -40°C ~ +80°C
- UV-INHIBITED PLASTIC TUBE
- STAINLESS STEEL MOUNTING HARDWARE (U-BOLTS, TOOTH BRACKETS, NUTS, SPRING WASHER)



MODEL NO	FREQ. (MHz)	GAIN (dBi)	DIMENSION (mm)
WY-2312	2300~2400	12	125 x 80 x 365
WY-2315	2300~2400	15	125 x 80 x 650
WY-2318	2300~2400	18	125 x 80 x 875
WY-2412	2400~2500	12	125 x 80 x 365
WY-2415	2400~2500	15	125 x 80 x 650
WY-2418	2400~2500	18	125 x 80 x 875
WY-2612	2500~2700	12	125 x 80 x 365
WY-2615	2500~2700	15	125 x 80 x 650
WY-2618	2500~2700	18	125 x 80 x 875

MODEL NO	FREQ. (MHz)	GAIN (dBi)	DIMENSION (mm)
WY-3512	3400~3600	12	
WY-3515	3400~3600	15	
WY-3518	3400~3600	18	
WY-5212	5125~5350	12	
WY-5215	5125~5350	15	
WY-5218	5125~5350	18	
WY-5812	5725~5850	12	
WY-5815	5725~5850	15	
WY-5818	5725~5850	18	